



GENERAL NOTES

1. SINGULAR® AERATOR, AS TESTED AND ACCEPTED BY NSF.
2. FALL THROUGH SINGULAR® PLANT FROM INLET INVERT TO OUTLET INVERT IS FOUR INCHES. INLET INVERT IS TWELVE INCHES BELOW TANK TOP.
3. ON DEEPER INSTALLATIONS, RISERS MUST BE USED TO EXTEND AERATOR MOUNTING CASTING AND BIO-KINETIC® SYSTEM MOUNTING TO GRADE. INSPECTION COVER ON PRETREATMENT CHAMBER MUST BE DEVELOPED TO WITHIN TWELVE INCHES OF GRADE.
4. TANK SHALL BE WATER TIGHT. WALL THICKNESS MAY VARY FROM THAT SHOWN.
5. REMOVABLE CONCRETE COVERS ON RISERS WEIGH IN EXCESS OF SEVENTY FIVE POUNDS EACH TO PREVENT UNAUTHORIZED ACCESS. PLASTIC COVERS ARE BOLTED TO RISERS.
6. TOTAL SYSTEM CAPACITY: 1800 GAL.

U.S. AND FOREIGN PATENTS GRANTED AND PENDING, NORWECO, INC.

File Name 750 GPD

SINGULAR® BIO-KINETIC®
WASTEWATER TREATMENT SYSTEM
MODEL 960
750 GPD TREATMENT CAPACITY
CLEAR WATER SOLUTIONS LLC
 KONA, HI
 Tel: 866 328 9265 Fax: 866 370 9265